




TWO-COMPONENT SYSTEM

RAMCO **EPOXY** **TILE** **GROUT**

is a durable, chemical-resistant filler for tile joints. Made of epoxy, it offers exceptional resistance to wear, making it perfect for areas prone to abrasion and impact. Ideal for filling gaps between various types of tiles, including glazed, ceramic, porcelain and natural stone, as well as glass mosaics.

Ramco Epoxy Tile Grout is a two-component product having epoxy resin, hardener and selected pigments in it along with advanced polymers.





Application areas

Suitable for grouting both floors and walls, indoors or outdoors. It can be used for bathrooms, kitchen, commercial, residential, etc.

It is suitable for a wide range of surfaces, including ceramic, glazed, porcelain, vitrified tiles.



Features

Low Maintenance:

Smooth texture for easy cleaning.

Chemical Resistance:

Excellent resistance to acids, and alkalis.

Hygienic and Tough:

Provides a durable, abrasion-resistant surface that maintains hygiene standards.

Water Resistance:

Offers water resistant joints.

Long-lasting:

Resists peeling, cracking, or powdering.

Mechanical Strength:


Withstands heavy traffic with excellent mechanical properties.

User-friendly:


Odorless, non-flammable and easy to clean with water.

It also works well with natural stones, large format tiles, glass mosaic tiles and composites, including engineered stones.

Instructions for use



1 Clean thoroughly on the tile joints area. Remove all the loose materials, oil, grease and other impurities.




2 Pour the content of Part B into container Part A for mixing.




3 Mix both components thoroughly till attaining a homogeneous paste.




4 Spread Ramco Epoxy Tile Grout – over float.



5 Fill the paste between tile joints within 1 hour of mixing and wait for 10 minutes for drying.



6 Use dry & clean float at a 45 degree angle to the tile surface to remove excess grout.



7 Clean the joints with the help of wet sponge to remove excess grout residue within 20 minutes of application and allow it to cure for 24 hours.

Component Appearance

Base (Part A) – Viscous Paste

Hardener (Part B) – Viscous Liquid

Mixed Material Consistency

Smooth Creamy Paste

Initial Setting Time

60 to 70 minutes

Coverage

15 – 16 running metre/kg (for 3mm X 3mm)

Right Products **for** Right Applications

