

RAMCO

# HARD WORKER



**BLOCK FIX** HW301



## FASTER AND STRONGER

- ★ STRONG BOND
- ★ HIGH COVERAGE
- ★ EASY APPLICATION

40KG

## Why HW Block Fix?

### FASTER AND STRONGER

For projects that demand speed and strength, Hard Worker Block Fix is the right choice. Just add water to the ready-to-use formulation. It bonds fast and clean while cutting down on time, effort and material. Just a 10 mm joint delivers high adhesion across red bricks, hollow and fly ash blocks, and stones. No on-site batching required. The result: faster walls, confident masonry, and a finish that holds up through time.

### STRONG BOND

Unlike cement-sand mixes, this blended dry mix mortar grips tight, reducing cracks and delays. HW301 is designed to build structural integrity from the first layer.

### HIGH COVERAGE

Spreads easy, bonds strong and covers more area. Reduces material loss and speeds up progress across large wall areas.

### EASY APPLICATION

Pre-mixed. Site ready. Just add clean water, mix and apply. The paste flows smooth, and keeps the blocks firm in place.

### COMPATIBLE

Engineered for various substrate types.

Substrate		Coverage in SQFT / 40 kg Thickness 10 mm
Red Brick		15 – 16
Fly Ash Brick		15 – 16
Solid Brick	4 inch	41 – 42
	6 inch	27 – 28
	8 inch	20 – 21
Laterite blocks	6 inch	34 – 35



POT LIFE



SPLIT TENSILE  
STRENGTH AT JOINTS  
0.2-0.35 MPa



WATER & TIME  
SELF-CURING

## APPLICATION



Add HW to water.

16-18% water by weight of HW301.



Mix to a thick paste.

Gradually mix with a slow speed blender.



Clean the blocks.



Apply 8 mm to 10 mm.

Apply evenly using a normal trowel.



Fix the blocks.

Press blocks firmly. Remove excess mortar.



Scan to watch Application Video.



Toll Free No: 1800 202 5700  
customer@ramcocements.co.in