

RAMCO

HARD WORKER



WATERPROOFING COAT

HW103



WATERPROOFING FOREVER

- ★ ARRESTS WATER SEEPAGE
- ★ ZERO CRACKING OF COAT
- ★ HIGH COVERAGE

3/ 15KG

Why HW Waterproofing Coat?

WATERPROOFING FOREVER

Zero seepage. Zero Cracks. Any construction is subject to climatic changes and is prone to the stress from expansion and contraction. Hard Worker Waterproofing Coat is a dual component formulation that is flexible under stress. It grips through temperature shifts, and forms a durable, watertight membrane that stays on.

Applied on the side from which water enters, the product stops ingress at the source, whether it is roofs, wet area walls, water tanks or basements. With just a thin layer that has high spread, it saves cost while delivering waterproofing that ensures structural integrity, for years.

ARRESTS WATER SEEPAGE

HW103 forms a watertight film. The dense, elastic film stops both surface water penetration and seepage from within the structure — be it rain, atmospheric moisture, standing water.

ZERO CRACKING OF COAT

The elastic film stretches without cracking, does not chalk, delaminate or split over time even under climatic changes. HW103 is engineered to withstand expansion and contraction.

HIGH COVERAGE

The interlocking dual polymer technology only needs a thin coat, that spreads evenly thus reducing material consumption and application costs.

VERSATILE APPLICATION

Suitable for vertical and horizontal surfaces. Works on new construction or renovation for concrete, mortar and masonry including brickwork and cement block substrates.

COVERAGE

HIGH

2 COATS
10 SQFT/kg
TOTAL THICKNESS 1 mm

HIGH

ELONGATION

90-100%

45
MINS

POT LIFE

APPLICATION



Fill cracks, clean and wet the surface.




Add components A and B to water.

Ratio by weight:
1 (Liquid) : 2 (Powder)
: 0.5 (Water)



Mix using a blender to a homogeneous mix.



Apply two coats (One horizontal, one vertical).

After first coat, keep surface dry and traffic free for 3-6 Hrs. Apply second coat.



Add protective screed/plaster.

After three days of air curing of second coat.



Scan to watch Application Video.



Toll Free No: 1800 202 5700
customercare@ramcocements.co.in